

# Domino C-Series

*Large character printers, for simple and cost-effective coding onto outer cases, trays and sacks.*



## Key Benefits:

### Maximum Performance and Reliability

- Proven valve jet technology ensures exceptional reliability and uptime
- 1litre of ink produces 1/2 million single line characters, enabling continuous coding and fewer bottle changes
- Pressurised ink system ensures reliable ink delivery for optimum performance

### Complete Flexibility

- Fully adjustable print head enables easy repositioning on production lines
- Interface stores up to 50 standard messages for quick set up wherever required

### Easy to Use

- Integrated user interface has simple keyboard layouts and a LCD display
- Icon based functions

### Easy to Install

- Compact and unobtrusive design
- Integrated print head bracket
- Integral photocell

## Main Features:

### Totally Efficient

- Box count facility
- Programmable time and date codes, shift codes and sell-by dates
- Real-time product counting
- Password protection for increased security

### Clean & Hygienic

- Clean and simple design is ideal for food and pharmaceutical industries
- Disposable ink containers reduces risk of leaks and mess
- Illuminated ink level display allows levels to be checked at a glance

### Environmentally Friendly

- Uses water based inks available in a choice of black, red, blue and green, provided in disposable containers



Small, compact and unobtrusive

## Technical Specification:

	C7	C16
<b>Character Heights</b>	10/17 mm (0.39/0.66")	10/14/20/32 mm (0.39/0.55/0.78/1.26")
<b>Maximum Line Speed</b>	35 m/min (115 ft/min)	35 m/min (115 ft/min)
<b>Print Resolution</b>	Standard print	Standard print
<b>Ink Capacity</b>	1 or 3-Litre (2.11 or 6.34 US pints)	1 or 3-Litre (2.11 or 6.34 US pints)
<b>Print Head Length</b>	249 mm (9.80")	247 mm (9.72")
<b>Print Head Width</b>	112 mm (4.40")	112 mm (4.40")
<b>Print Head Depth</b>	88 mm (3.46")	108 mm (4.25")
<b>1-Litre Base</b>		
<b>Ink Base Height</b>	315.5mm (12.42")	315.5mm (12.42")
<b>Ink Base Width</b>	155 mm (6.10")	155 mm (6.10")
<b>Ink Base Depth</b>	110.5 mm (4.35")	110.5 mm (4.35")
<b>3-Litre Base</b>		
<b>Ink Base Height</b>	328.5 mm (12.93")	328.5 mm (12.93")
<b>Ink Base Width</b>	173mm (6.81")	173mm (6.81")
<b>Ink Base Depth</b>	110.5 mm (4.35")	110.5 mm (4.35")
<b>Unit Weight (200ml)</b>	N/A	N/A
<b>Unit Weight (1-Litre)</b>	8.2 Kg (18.07 lbs)	8.4 Kg (18.51 lbs)
<b>Unit Weight (3-Litre)</b>	11 Kg (24.25 lbs)	11.2 Kg (24.69 lbs)
<b>Construction</b>	Stainless steel	Stainless steel
<b>Electrical</b>	90 – 240 V @ 50 – 60 Hz	90 – 240 V @ 50 – 60 Hz
<b>Operating Temperature</b>	5° – 35° C (41° – 95° F)	5° – 35° C (41° – 95° F)
<b>Humidity (Non-condensing)</b>	10%-90%	10%-90%
<b>Options</b>	External photocell, Arabic characters	External photocell, Arabic characters